

## Ductless/Mini-Split Heat Pump with Electric Back-Up - Check List

Member/Customer Name							
Member/Customer Address							
Make		Model #	Serial #				
Contractor Name			Service	ervice Date		Auxiliary Resistance (kW)	
Check Off If Done	If any item cannot be checked or recorded, please provide an explanation. (For example, "No temperature/pressure Pete's plugs in loop piping.")						
	Check air filter and change if required.						
	Check relays and contactors and for loose electrical connections.						
	Calibrate thermostats.						
	Clean outdoor coil.						
	Check outdoor fan for proper operation, or damage, and lubricate as required.						
	Clean Indoor coil.						
	Check drain pan and trap for blockage or leaks. Flush the condensate drain.						
	Check blower assembly for proper operation, or damage, and lubricate as required.						
	Check static air pressure and record.					in. WC	
	Check air supply temperature in heating temperature difference.	mode and record. Calculate supply – re	turn		۴	Sup-Ret Δ °F	
	Check air return temperature in heating manufacturer specifications.	mode and record. Compare temperatur	re differer	nce to	۴	Mfg. Spec. Δ °F	
	Check air supply temperature in cooling temperature difference.	mode and record. Calculate supply – ret	turn		۴	Sup-Ret Δ °F	
	Check air return temperature in cooling manufacturer specifications.	mode and record. Compare temperatur	e differen	nce to	۴	Mfg. Spec. Δ °F	
	Compare static pressure and temperatures to manufacturer specifications and adjust blower speed settings if required and record final pressure and temperatures.						
	If air temperature deltas are not per manufacturer specifications, measure refrigerant levels and charge as required. Recheck and record temperatures if charged.						
	Measure compressor volts and record. C	Compare to manufacturer specifications.			Volts	Mfg. Spec. Volts	
	Measure compressor amps and record.	Compare to manufacturer specifications	5.		Amps	Mfg. Spec. Amps	
	Check back-up resistance heat staging.						
	Check air supply temperature in back-up temperature difference.	heating mode and record. Calculate su	pply – ret	urn	°F	Supply-Return Δ °F	

	neck air return temperature in in back-up heating mode and record. Compare temperature fference to manufacturer specifications.	°F	Mfg. Spec. Δ °F
Ch	Check and record cut-out or switch over temperature if applicable.		
lf h	humidifier, clean, check control and adjust as required.		